

BananaPi R3

https://wiki.banana-pi.org/Banana_Pi_BPI-R3_Mini

Hardware

- MT7986(Filogic 830) quad core ARM A53 SoC
- 2G DDR RAM
- 8G eMMC flash, SPI-NAND (128 MiB)
- 2x 2.5GbE network port (airoha en8811h phy)
- dual-band wifi:
 - 2.4G
 - 5G



debug-uart

connections from the edge of board: GND,RX,TX (remember RX/TX swap on your adapter :))

Software

my R3mini came preinstalled with vendors openwrt (21.02-SNAPSHOT, Linux version 5.4.171) on emmc and nand. i suggest to leave the nand to have always a rescue-system and only flash emmc as productive system with a more recent version.

It will take some time till i can release a full emmc-image for R3 Mini, but my uboot-repo generates already a very basic bpi-r3 emmc image (Releases Page) without rootfs/kernel which can be used on r3mini as well. Userspace can generated with the buildchroot.sh of my BPI-Images Repo or extracted from a full r3 Image.

Step-by-step:

used usb-stick to get files accessible from r3mini

started with r3-img:

```
gunzip -c /mnt/sda2/bpi-r3_bookworm_nokernel.img.gz |dd bs=1024  
conv=notrunc,fsync of=/dev/mmcblk0
```

then flash uboot (wonder why there is no mmcblk0boot0 block to flash the bl2 - seems to be a problem with vendor-image, in my linux i see the boot0):

```
#r3mini/bl2_r3mini_emmc_pcie.img to boot0 conv=notrunc,fsync
dd if=/mnt/sda1/r3mini/fip_r3mini_emmc_pcie.bin bs=1024 conv=notrunc,fsync
of=/dev/mmcblk0p4
```

Kernel (creates the bpi-r3.itb with conf-emmc-mini bootconfig):

<https://github.com/frank-w/BPI-Router-Linux/tree/6.6-r3mini>

need to drop the „run setbootconf;“ from newboot first

```
BPI-R3M> run useusb
BPI-R3M> setenv initrd rootfs.cpio.zst
BPI-R3M> setenv fit r3mini/bpi-r3.itb
BPI-R3M> setenv bootconf "#conf-emmc-mini"
BPI-R3M> run newboot
```

how to get available bootconfigs from binary fit image:

```
dumpimage -l /media/frank/Android-x86/r3mini/bpi-r3.itb
```

vendor-kernel

DTS for reference:

<https://github.com/BPI-SINOVOIP/BPI-R3MINI-OPENWRT-V21.02.3/blob/main/target/linux/mediatek/files-5.4/arch/arm64/boot/dts/mediatek/mt7986a-bananapi-bpi-r3mini-emmc.dts>

chainload uboot

```
BPI-R3M> fatload usb 0:1 $loadaddr r3mini/u-boot-pcie.bin
815592 bytes read in 73 ms (10.7 MiB/s)
BPI-R3M> go $loadaddr
## Starting application at 0x46000000 ...
U-Boot 2024.01-bpi-r3mini-00011-g5aadabca11e5-dirty
```

pcie/nvme

working in my r3mini uboot (2024-01-bpi-r3mini)

```
BPI-R3M> pci enum
drivers/pci/pcie_mEDIATEK_gen3.c:mtk_pcie_startup_port[261] detected a card
set trans table 0: 0x20000000 0x20000000, 0x10000000
BPI-R3M> pci
```

BusDevFun	VendorId	DeviceId	Device Class	Sub-Class
00.00.00	0x14c3	0x1f32	Bridge device	0x04
01.00.00	0x1c5c	0x1327	Mass storage controller	0x08

```
BPI-R3M> nvme scan
BPI-R3M>
BPI-R3M> nvme info
Device 0: Vendor: 0x1c5c Rev: 80002C00 Prod: ND94N163610404F0R
          Type: Hard Disk
          Capacity: 244198.3 MB = 238.4 GB (500118192 x 512)
BPI-R3M>
```

network support

only working once then network is stalled

```
BPI-R3M> setenv ipaddr 192.168.90.2
BPI-R3M> ping 192.168.90.1
Using ethernet@15100000 device
host 192.168.90.1 is alive
BPI-R3M> ping 192.168.90.1
Using ethernet@15100000 device

ARP Retry count exceeded; starting again
ping failed; host 192.168.90.1 is not alive
BPI-R3M>
```

we will wait till phy driver is in linux mainline and use this as base for rewriting uboot driver

Fix bricked boot

In case nand and emmc are broken there is a way to load uboot via uart for reflash/fix bootchain of the storages.

<https://forum.banana-pi.org/t/bpi-r3-mini-boot-from-nand-fails/17340/24>

Currently untested by me

From:

<http://fw-web.de/dokuwiki/> - **FW-WEB Wiki**

Permanent link:

<http://fw-web.de/dokuwiki/doku.php?id=en:bpi-r3mini:start&rev=1709318405>

Last update: **2024/03/01 19:40**

